

Pitch: 5.08mm(0.200inch)





SPECIFICATIONS


			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 300V	AC 450V
負載電流	Rated Current	Bemessungsstrom	16A	16A
電線線徑	Wire Size	Leitergrößen	26~12AWG	0.2~2.5mm ²
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
押線圈	Cage Clamp	Klemmkörper	Brass, Ni plated	
端子	Terminal	Stiftmaterial	Brass, Tin plated	
螺絲	Screw Size	Schraubengewinde	M2.6, steel, Ni plated	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
扭力	Torque	Anzugsmoment	5.0 lb-inch	
PC板孔徑	PCB Hole Diameter	Lochdurchmesser	φ 1.5mm	
UL File No.	E167040			

TABLE

Item No.	A(mm)	A(inch)
MB312-508M02	10.2	0.400
MB312-508M03	15.2	0.600



PCB Layout



Note:
 Screw Plating: Changes are available upon request
 Cage Clamp: MB 310: Steel
 MB 311: Zinc